



A M E R I S E R V

Water Technology

PRODUCT DATA SHEET

CWT 33 - COMPLETE COOLING WATER TREATMENT

GENERAL DESCRIPTION:

CWT 33 is a concentrated cooling water treatment used as a scale retardant, antifoulant and corrosion inhibitor. CWT 33 contains an efficient dispersant of common inorganic particulates found in cooling tower systems. CWT 33 is authorized by the United States Department of Agriculture for use in federally inspected facilities.

PRODUCT CHARACTERISTICS:

Form.....Light Golden Liquid
pH.....Approximately 12.0
Density.....9.12 lbs./gallon

FEEDING:

CWT 33 may be pumped directly from the shipping container into a recirculating cooling water line or fed directly to the tower basin. A proportional feed and bleed system controlled by a conductivity controller is recommended. Consult your service representative for specific recommendations.

PRECAUTIONS AND HANDLING:

Product is an alkaline material. Avoid contact with skin and eyes. Do not take internally. Protective gloves and chemical splash goggles are recommended. Wear impervious apron and boots to minimize potential contact. General ventilation is adequate, however, a NIOSH approved breathing apparatus should be used for exposures above OSHA threshold limit values. Consult material safety data sheet for more information.

PACKAGING:

55 GALLON DRUMS
30 GALLON DRUMS
5 GALLON PAILS

Post Office Box 65010 Orange Park, Florida 32065-5010
Phone (407) 461-8496 Fax (407) 788-3999