

- DESIGNED SPECIFICALLY FOR THE NEED OF HUMIDORS
- Humidifies using electronic dispersion of water molecules
- No added heat load to the Humidor or facilities Air Conditioning system
- USES ONLY 250 watts-120 times less than conventional systems
- USES ONLY 250 watts-ONLY while actually humidifying
- Infinite ducting options - Built for inside or outside Humidor
- Minimum Reliability of 50,000 hours of humidification time
- Network, WIFI, and Bluetooth, Remote Control Enabled
- Interfaces directly with building management systems
- Small footprint-compact size: 24"H x 24"W x 14"D
- No sediment to dispose of or foul the system
- No high temperatures - No High Pressures
- Accurate Humidity control to +/- 2 %
- Built-in Water Purification System
- Industrial Grade Stainless Steel
- Plugs into simple 115VAC outlet
- Costs pennies a day to operate
- Broadcast alert/alarm system
- Full Data Logging capability
- Automatic Self Cleaning
- Floor and wall models
- Only 4 moving parts
- Operates silently



## HUMATADOR MINI® SPECIFICATIONS

HUMIDITY RATING	0.15 TO 60# PER DAY
POWER REQUIREMENTS	120VAC/60 – 2 AMPS
DIMENSIONS	24"W x 24"h X 14"D
FEEDWATER REQUIREMENTS	¼" CITY WATER @ 35-psi And FLOOR DRAIN

## ALARMS

- High level alarm and shutoff
- Low level alarm and shutoff
- Out of tolerance of humidity alert
- Routine service alert
- Alarm service alert by email
- Water quality monitoring
- Custom alerts



**ADVANCED WATER ENGINEERING, INC.**  
**INDIAN HARBOUR BEACH, FL 32937**  
**(321)777-4909 FAX: (321)773-8338**

WWW.HUMATADOR.COM

www.advancedwater.com

INFO@ADVANCEDWATER.COM INFO@HUMATADOR.COM